

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600568

PRIMARY CORNER DESCRIPTION MC on line between Secs. 11 & 12

Alias <u>968180</u>	Description <u>MC East shore Loon Lake</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2707)

Intersect lake. Marked a Yew, 24" dia., for the Meander cor. & witness corner to secs. 1, 2, 11, & 12. No witness trees convenient. Sec. cor. in lake.

GL0 survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2756)

At point of intersection with high water mark in lake, I set a stone, 30x24x6 ins. 24" in the ground, for meander corner of frac. secs. 11 & 12, marked MC on N with 1 groove on E face, from which
 A Fir, 6" dia., bears S.10°E., 13 lks., mkd: T23S R10W S12
 MC BT.
 A Fir, 8" dia., bears S.11°W., 16 lks., mkd: T23S R10W S11
 MC BT.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 52 (Filed 4/24/1958 C.S. File 49/80)

Set - 3"x3"x3' Fir post at high water mark of lake for MC of secs. 11, 12 T23S R10W from which
 An 8" Fir, bears N.78°E., 28.5 ft.
 A 24" Fir bears S.19°W., 39.0 ft.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - March 1958 - C.S. File 49/90 (pg 3)

Found - Fir tree, now 32" S.19°W., 39.0 ft. This tree has been chopped open exposing face & scribe marks "S11 T23 R10W" ring count shows this to have been scribed approx. 20 years ago.
 Fir tree, now 16" N.78°E., 28.5 ft. showing good scar. Did not chop this tree open.
This corner falls in road fill in slide area.
At corner set Fir post 4"x4"x10" scribed "MC S11" on West side, "MC S12" on East side and "CS" on South side.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Dec. 1966 - C.S. File 49/63-5

Found - 4"x4"x10" Fir post, nearly rotted off at ground, & BTs as recorded in 1958, as follows:
continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600568

PRIMARY CORNER DESCRIPTION MC on line between Secs 11 & 12

Alias 968180 Description MC East shore Loon Lake

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

32", now 34" Fir, alive, S.19°W., 39.0 ft., prev.
opened, blaze well pitched over.
16", now 18" Fir, alive, N.78°E., 28.5 ft., shows
good scar. Do not open
Set - Brass cap at cor mkd: County Surveyor's T23S R10W
Office 1966 MC S11/S12
Note - This corner lies approx. 10 ft. south of water's
edge on steep, NW slope.