

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600629

PRIMARY CORNER DESCRIPTION MC on line between Secs. 1 & 2

Alias <u>968240</u>	Description <u>MC North shore Loon Lake</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2709)  
-----  
Intersect lake marked an Ash, 4" dia., for the meander corner between secs. 1 & 2, from which  
    A Fir, 18" dia., bears N.20°E., 70 lks.  
    A Fir, 24" dia., bears N.45°W., 60 lks.

GL0 survey by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2758)  
-----  
I begin at the meander cor. of frac. secs. 1 & 2 on the NE shore of Loon Lake, which is an Ash tree, 7" dia. The blazes are much defaced by action or waves. It was blazed on South, East and West faces; the following marks are legible: S1 on E, S2 on W.  
From this tree,  
    An Ash, 8" dia., bears N.5°W., 8 lks., mkd: S2 BT.  
I mark cor. tree MC on S., T23S on N., R10W S1 on E., and S2 on W., from which I mark a new tree.  
    An Ash, 11" dia., bears S.34°E., 46 lks., mkd: T23S R10W MC BT.  
This corner tree was 4" dia., when marked, and is evidently the true meander cor., but I could find no trees corresponding with those described by the Surveyor General.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 52 (Filed 4/24/1958 C.S. File 49/80-1 pg 9)  
-----  
Sighted across lake & set stake at water's edge  
Set - 4"x4"x4' Fir post  
    12" Ash S.6°E., 22 ft.  
    10" Ash N.63°W., 13 ft.