

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 607700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only, T22-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 292 survey dated Aug. 7, 1878 (DCSO records Vol. 4 Page(s) 1740-41)

Set a Fir post, 4 ft. long, 4" dia., 20" in ground for ¼ sec. cor. on S. bdy. of sec. 36, from which,
A Fir 36" dia., bears N.65°E., 57 lks. dist.
A Fir 8" dia., bears S.62°W., 42 lks. dist.

Cor. fd. and used in GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1755)

Survey by Daniel Baker - For: International Paper Co. - April 1987 - M 104-19 and C.S. File 63/50-7

Set a 5/8" x 30" Iron rod and cap.
BTs - 18" Fir bears N.4°E., 38.1 ft. scribed ¼ S36 BT.
18" Fir bears N.80°E., 38.5 ft. scribed ¼ S36 BT.
Distances to 7" spike in side and center, bearings magnetic Var. 20°.