

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO recs. Vol. 7 Page(s) 2702)

Set Hemlock post, 4 ft. long, 5 ins. dia., 18" in ground for the 1/4 sec. cor. between secs. 25 & 36, from which
 A Hemlock, 36" dia., bears S.20°E., 12 lks.
 A Hemlock, 30" dia., bears N.20°W., 30 lks.

Fd. by Theodore S. Ellingsen - For: Menasha Wooden Ware Corp. - Nov. 18, 1954 - C.S. File 41/327

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Aug. 1957 - C.S. File 49/60

Found - Tags at cor. & possible scribe marks on possible old face of large & rotted hemlock stump S.20°E. 7.9' Also fd. rotted hemlock stump that checked within 2' for position of NW BT. Badly rotted. No face fd. I checked calls East to Lake Creek which indicates cor., 4"x4" sq. stake, should be about 70' West of present location.
I do not renew this corner.

Michael S. McDowell - For: Weyerhaeuser Company - Dec. 1, 1976 - M 62-48 - C.S. File 58/128

Found - 3" square fir stake, from which
 A 20" Hemlock stub, badly rotted bears S.20°E., 8.5 ft. (rec. 36", S.20°E., 12 lks.)
 An 18" Hemlock stub, badly rotted bears N.20°W., 22.6 ft. (rec. 30", Hemlock N.20°W., 30 lks.)
Set - I place a 2" gal. IP with brass cap at the point mkd. by the stake from which:
 A 16" Hemlock scribed BT bears S.61°E., 21.4 ft.
 A 14" Fir scribed BT bears N.45°W., 9.1 ft.

Fd. Ok by T. Hostetter, 8/1996 M 126-31
Fd. OK by C. Sweeden, April 2004 - M144-24
Fd. 2" IP by N. Hibbs, 11/2007 - M146-70
Fd. Ok by Estabrook Land Surveying - 5/1/2025 - M186-3