

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2877) and duplicate Page 2765)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 7 and 12 marked T24S S6 on NE.; R1W S7 on SE.; R2W S12 on SW.; and S1 on NW. faces, with 1 notch on N. and 5 notches on S. edges, from which

- A Fir 10" dia., bears N.15°E., 82 lks. dist. mkd. T24S R1W S6 BT.
- A Fir 6" dia., bears S.31°E., 16 lks. dist. mkd. T24S R1W S7 BT.
- A Sugar Pine 10" dia., bears S.42°W., 8 lks. dist. mkd. T24S R2W S12 BT.
- A Sugar Pine 6" dia., bears N.27°W., 6 lks. dist. mkd. T24S R2W S1 BT.

Fd. and tied Corner in GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2942)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept. 18, 1969 - C.S. File 54/27-236

 Found - Orig. 10" now 30" Fir, alive, N.15°E., 54.1 ft., bark scribe, poor.
 Orig. 10" now 18" S.Pine, dead, S.42°W., 5.3 ft., scribe visible.
 Orig. 6" now 16" S.Pine, alive, N.27°W., 4.0 ft., shows faint scar. Rescribe "T24S R2W S1 CS BT"
 No trace of original SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office

| | | |
|---|------------|---|
| R | T 24 S | R |
| 2 | S 1 S 6 | 1 |
| W | S 12 S 7 | W |

1969

New BTs- 9" Sugar Pine N.15°E., 5.0 ft. mkd. T24S R1W S6 CSBT
 13" D.Fir S.72°E., 26.7 ft. mkd. T24S R1W S7 CS BT.
 13" D.Fir S.70°W., 24.0 ft. mkd. T24S R2W S12 CS BT.
 Corner lies on top of spur, sloping South.

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1533, Surveyed May 1990 - (DCSO records Vol. 50 Page(s) 18996-97)

The Sec. Cor., perpetuated and recorded by Tracy in 1969, subsequently recovered by Ness in 1980, monumented with an (Cont. Next Page)

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T24-2

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

iron post, 1¼" dia., firmly set, projecting 10" above ground with brass cap as mkd. by County in 1969

from which the remains of the original bearing trees:

A Fir 30" dia., bears N.15°E., 80 lks. dist., with old axe marks on the bark. (Rec. 82 lks.)

A rotted Pine stump 16" dia., bears S.42°W., 8 lks. dist. no marks remaining

A Pine snag, 14" dia., bears N.27°W., 6 lks. dist., with scribe marks T24S R2W S1 CS BT on a partially healed blaze.

and the remains of bearing trees mkd. by Tracy

A Pine snag 8" dia., bears N.18°E., 8 lks. dist., with scribe marks T24S R1W S6 CS BT visible on a partially healed blaze.

A Fir 18" dia., bears S.72°E., 40 lks. dist. with healed blaze.

A Fir stump 18" dia., bears S.70°W., 36 lks. dist. with healed blaze. The stump is 7 ft. high with a metal cap.

and a new bearing tree:

A Fir 18" dia., bears N.37°W., 22 lks. dist. mkd. T24S R2W S1 BT.

Corner is on a South slope at the NE. corner of a clearcut logged area.

From this point, National Geodetic Survey Triangulation Station "HUCKLE" 1953-1970", bears N.82°25'30"E., 57.425 chs. dist. The station is monumented with a bronze tablet, 3" dia., cemented into solid rock, found in good condition beneath a concrete slab, 8" thick, 6 ft. dia., which was broken through during this survey. All reference monuments have been destroyed.