

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 1, T24-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2878) and duplicate Page 2766)

-----  
Set a Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which  
A Fir 24" dia., bears N.25°E., 13 lks. dist. mkd. ¼ S BT.  
A W.Fir 20" dia., bears N.80°W., 38 lks. dist. mkd. ¼ S BT.

Cor. Fd. and tied in GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2942)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew August 1969 - C.S. File 54/27-263

-----  
Found - Orig. 24" now 48" Fir, alive, N.25°E., 8.6 ft., "BT" bark scribe visible on lower blaze, upper blaze mostly gone.  
Orig. 20" now 24" W.Fir, alive, N.80°W., 25.1 ft., very faint scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S  
R2W ¼ S 1 | S 6 R1W  
1969

New BTs- 14" W.Fir S.41°W., 10.0 ft. mkd. ¼ S1 CS BT.  
8" W.Fir N.54°E., 28.2 ft. mkd. ¼ S6 CS BT.

Corner lies 60 ft. South of 2 ft. wide creek, course SW.