

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2846)

Set a basalt stone 16x14x12" 12" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which

A fir, 12" dia., bears S.52°E., 5 lks., mkd: 1/4 S BT.

A fir, 12" dia., bears N.19°W., 40 lks., mkd: 1/4 S BT.

This cor. is on a steep hillside, sloping W about 25 ft. below spur last noted.

Douglas Co. Surveyors Office - Larry E. Monrean - R.B. Kimberling - S.J Flause - P.L Earle - May 1977 - C.S. 59/34-6

Found - Orig. basalt stone at 1/4 cor. Stone is 16"x14"x12" firmly set & marked "1/4" on northerly face.

Orig. 12" Fir now an uprooted snag bears S.52°E., 3.3 ft. Tree has healed scar with the face rotted out, no scribing

Orig. 12" now 30" Fir & uprooted bears N.19°W., 26.4 ft. Tree has well healed blaze. We do not open for scribing.

Set - 1"x30" iron pipe with brass cap attached mkd:

DOUGLAS COUNTY SURVEYOR T24S R1W
1977 1/4 S 19
S 30

Set orig. stone along north edge of cap.

New BTs- 9" Hemlock bears N.5 1/2°W. 42.9 ft. Tree double blazed & "1/4 S19 CS BT"

28" D.Fir bears N.83 1/2°E., 14.4 ft. Tree double blaze & scribed "1/4 S19 CS BT" Marked for high stumping.

Set RR spike in a 59" Fir stump, spike bears S.66 1/2°W., 71.6 ft. Spike marked "BO"

Fd. & used on BLM Dependent resurvey by James E. Jelley & Wayne L. Rogers, Cadastral Surveyors under Group #1051 surveyed April 1981/Sept. 1982 - (DCSO records Vol. 45 Page(s) 17338)