

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCS0 recs Vol. 7 Page(s) 2851)  
-----  
Set a basalt stone 14x12x8" 9" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which  
    A fir, 14" dia., bears N.68°E., 17 lks., mkd: 1/4 S BT.  
    A fir, 34" dia., bears S.35°W., 12 lks., mkd: 1/4 S BT.  
This cor. is on a steep hillside, sloping W abut 175 ft. below spur.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April 2, 1968 - C.S. File 54/42-61  
-----  
Found - 14x12x8" corner stone, out of position due to SW orig. BT turning out. Stone mkd: "1/4"  
    Orig. 14" Fir, now 16" snag, N.68°E., 11.2 ft., open & find "BT"  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W OFFICE 1968 1/4 S 18 S 19  
    (Reset orig. cor. stone alongside)  
New BTs- 8" Hemlock N.0 1/2°W., 14.9 ft., mkd: 1/4 S18 CS BT.  
    5" Hemlock S.43°W., 38.5 ft., E of small creek, course North.  
Note - This corner lies 35 ft. E of small creek, course North.

Dan Saily- For: Lone Rock - 12/2023 - C.S. File 65/112-5  
-----  
Found - 1968 Douglas Co. Surveyor's brass cap (properly mkd) as per C.S. 54/42-61. Top of monument is 0.8 ft above ground and lies 33 ft east of creek running North South,  
    21" W.Hemlock found at record N.0 1/2°W., 14.9'. Healed face, we tag.  
New - 22" W. Hemlock bears S.63 1/2°W., 18.2'. We scribe 1/4 S19 BT & Tag.  
    7" D.Fir bears S.4°E. 43.3' We scribe S19 X BT & tag  
    18" W. Hemlock bears N.68°W., 40.5'. We scribe S18 X BT and tag.  
We place a 5 1/2' tall steel galvanized U-Post 1' West.  
We did not locate the other record BTs or the original stone.