

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2856)

Set a basalt stone 12x8x8" 8" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which

A fir, 12" dia., bears N.65°E., 12 lks., mkd: 1/4 S BT.

A fir, 24" dia., bears S.33°W., 7 lks., mkd: 1/4 S BT.

This 1/4 sec. cor. is on a steep hillside, sloping S about 75 ft. below ridge.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Clete Putnam - June 15, 1962 - C.S. File 52/42-17

Found - Rock set by Nicklin in 1896. Rock mkd: "1/4" on N face

D.Fir now 30" S.33°W., 4.6 ft. Very plain axe scar.

Reblaze & scribe this tree "1/4 S18 CS BT"

D.Fir now 17" N.65°E., 7.9 ft., good axe scars visible. Reblaze & scribe this tree "1/4 S7 CS BT"

Along N side of Rock at corner set brass cap for corner mkd:
County Surveyors Office 1962 T24S R1W 1/4 S7/S18