

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2839)

Set a basalt stone 12x10x8" 8" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A cedar, 16" dia., bears N.23°E., 65 lks., mkd: ¼ S BT.

A fir, 10" dia., bears N.52°W., 17 lks., mkd: ¼ S BT.

This cor. is on a steep hillside, sloping SE about 200 ft. above creek.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - May 27, 1970 - C.S. File 54/27-192

Found - Corner stone mkd: "¼" on W face.
Orig. 10" now 24" Fir, alive, N.52°W., 11.2 ft. shows scars. We rescribe "¼ S31 CS BT"

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W (reset old stone alongside) OFFICE 1971 ¼ S31|S 32

New BT - 42" Fir stump, N.11°E., 57.1 ft. mkd: "¼ S32 CS BT"
There are no trees east of line.

This corner lies on very steep SE slope on N-S cutting line, S32 clearcut.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Randall W. Smith - Oct. 18. 1983 - C.S. File 62/7-4

Found - Iron pipe with 1970 county brass cap, properly mkd., protruding 18" above ground.
DID NOT find orig. basalt corner stone.
Orig. 10" fir, now 26" dia., bears N.52°W., 11.2 ft. partially healed blaze with scribing visible.
42" fir stump bears N.11°E., 55.8 ft., (rec. 57.1 ft.) no scribing visible. 1970

Set - Monument was protruding 18" above ground on steep rocky hillside. We made a mound of rocks approx. 5 ft. x 4 ft. around monument to protect it.

New - Set a 8"x½" spike in a 42" fir stump bears N.11°E., 55.0 ft. Spike set through a "DOUG. CO. SURVEYORS OFFICE" BT tag in pitch ring of stump. (Stump is a BT from 1970)

A chiseled "X" in face of rock bluff, bears S.48°W., 14.5 ft.

Note - Corner lies on steep east slope approx. 300 ft. east of BLM rd. #25-1-5.4. Corner lies in cutting line. A clear cut is to the east of corner.

continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Gerald V. Nygren - For: Barnes & Assoc. Inc. - 11/2016 - M172-62

Found - 1971 C.S. brass cap per PLSS 200140
(1890 10" Fir, now 30" bears N.52°W., 11.2' healed face.
(1970) 42" Fir stump bears N.11°E., 55.8' no marks visible
(1983) Chiseled "X" in face of rock bluff bears S.48°W., 14.5'