

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2848)

Set a dogwood post, 3½ ft. long, 4" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W face, from which
 A fir, 30" dia., bears N.28½°E., 30 lks., mkd: ¼ S BT.
 A fir, 30" dia., bears S.56°W., 55 lks., mkd: ¼ S BT.
This cor is on a hillside, sloping SW about 100 ft. above last point of crossing creek.

Howard Johnstone - Roseburg Lumber Co. - 3/31/1977 - M 65-15

Set - 5/8"x40" iron rod & alum. cap.
BTs - 42" Fir, N.28½°E., 19.8 ft. OBT
 44" Fir, S.56°W., 36.3 ft. OBT

Fd. & used on BLM Dependent resurvey by James E. Jelley & Wayne L. Rogers, Cadastral Surveyors under Group #1051 surveyed April 1981/Sept. 1982 - (DCSO records Vol. 45 Page(s) 17341)