

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs 17, 18, 19, & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2848-9)  
-----  
Set a basalt stone, 20x16x8" 16" in the ground, for cor. of secs. 17, 20, 19, & 18 marked with 3 notches on S & 5 notches on E edges; from which  
A fir, 16" dia. bears N.70°E. 44 lks. mkd: T24S R1W S17 BT  
A fir, 20" dia. bears S.63°E. 24 lks. mkd: T24S R1W S20 BT  
A fir, 12" dia. bears S.45°W. 20 lks. mkd: T24S R1W S19 BT  
A fir, 18" dia. bears N.47°W. 15 lks. mkd: T24S R1W S18 BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy-Vernon Tracy - Clete Putnam - Oct. 1961 - C.S. File 52/42-9  
-----  
Found - Rock as called for in Gov't notes, it has slid down hill approx. 2 ft. from corner.  
Fir tree, now 26" N.47°W., 9.9 ft. Good scars, has been partially chopped open, scribing visible "S18"  
Fir tree, now 24" S.63°E., 15.8 ft. Shows good scars did not chop open.  
Fir tree, now 20" N.70°E., 29.0 ft. Shows good scars did not chop open.  
Dead fir snag S.45°W., 13.2 ft. scribing visible "4S R1W S19"  
Set - Brass cap mkd: COUNTY SURVEYORS T24S R1W S 18|S 17  
(Set orig. rock alongside) OFFICE 1961 S 19|S 20  
New BT - 8" Hemlock S.49°W., 8.5 ft. mkd: T24S R1W S19 CS BT.

BLM Dependent resurvey by James E. Jelley & Wayne L. Rogers, Cadastral Surveyors under Group #1051 surveyed April 1981/Sept. 1982 - (DCSO records Vol. 45 Page(s) 17341-2)  
-----  
The cor. of secs. 17, 18, 19, & 20, perpetuated & recorded by Godfrey in 1961 monumented with an iron post, 1¼" dia. firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the orig. BTs:  
A fir 22" dia. bears N.70°E., 44 lks. with a healed blaze.  
A sawed fir stump, 25" dia., bears S.63°E., 24 lks., with a healed blaze.  
A sawed fir stump, 14" dia., bears S.45°W., 20 lks., with axe marks visible on an opened blaze.  
A sawed fir stump, 26" dia., bears N.47°W., 15 lks., with scribe marks S18 visible on an opened blaze.  
and a BT mkd. by Godfrey  
A hemlock, 10" dia. bears S.49°W., 13 lks., with fragmentary scribe marks visible on partially healed blaze.  
continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor Secs 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new BTs

A hemlock, 8" dia., bears S.5½°E., 40 lks., mkd: T24S R1W S20 BT.

A hemlock, 8" dia., bears N.73½°W., 43 lks., mkd: T24S R1W S18 BT.

Dan Saily, Lone Rock Timber - Crew: Brett Ragon, Brodie Minter & Trevor Clemo - 2/2025 - M184-56

- 
- Found - 2½" DCSO brass cap & iron pipe (properly mkd)  
16" W.Hemlock bears S.5¾°E., 25.8', 1981 rec S.5½°E., 26.4' (40 lks), with a well healed face. We tag.  
24"x7' tall D.Fir stump bears S.63¼°E., 15.7', rec 1981 BLM S.63°E., 15.84' (24 lks), with a well healed face and BLM tag.  
16" W.Hemlock bears S.49¼°W., 8.3', 1981 BLM rec S.49°W., 8.58' (13 lks), with a well healed face and BLM tag.  
16" W.Hemlock bears N.73¼°W., 28.5', 1981 BLM rec. N.73½°W., 28.38' (43 lks), with a well healed face. We tag.  
25"x 5.5' tall D.Fir stump bears N.51¼°W., 9.8', 1981 BLM rec. N.47°W., 9.9' (15 lks), with a visible scribe "S18" and BLM tag.  
21"x8' tall D.Fir stump bears N.70¼°E., 28.8', 1981 BLM rec. N.70°E., 29.04' (44 lks), with a well healed face and BLM tag.

Corner monument lies on a steep NW facing slope in mixed age timber stand, approximately 150' South of gravel surfaced BLM logging road. Top of monument is 0.7' above ground level. We place a 5½' tall galvanized, steel U-post 1.0' North.

BTs were scribed at root crown with distances measured to an alum. nail at side center & BTs were computed by turning horizontal angles from traverse control point to an alum nail in face center.