

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GL0 survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2853)

Set a madrona post, 3½ ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:
 A fir, 14" dia., bears N.37°E., 19 lks., mkd: ¼ S BT.
 A fir, 54" dia., bears N.30°W., 23 lks., mkd: ¼ S BT.
This cor. is on a steep hillside, sloping SE about 100 ft. above creek last noted.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy; M. Stone, crew - July/Aug. 1962 - C.S. File 52/42-20

Found - Ponderosa Pine (instead of Fir) 17" dia., N.37°E., 12.5 ft. Opened scar & fd. good scribing "¼" 54" dbl. sugar pine (instead of Fir) N.30°W., 15.2 ft. Two very plain scars.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1962 T24S R1W ¼ S18|S17
Blaze & scribe 1 new BT
21" D.Fir N.23°E., 24.0 ft. mkd: ¼ S17 CS BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 15, 1967 - C.S. File 52/42-55

Found - 1962 Co. Surveyor brass cap & BTs, properly marked. Both orig. BTs now turned out & slid down very steep, SE slope.
21" D.Fir N.23°E. 24.0 ft. alive, face pitched over
New BT - 28" D.Fir S.40°W., 44.8 ft. mkd: ¼ S18 CS BT.
Note - This corner lies on steep, SE slope.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/10/2024 - C.S. File 67/59-27

Found - 2½" DCSO brass cap (properly mkd) on 1" ID IP, proj 8" in rough mound of stone, badly bent 0.6 ft ≈ S.50°E. Fd monument's plumb position referenced, removed and straighten. Reset monument to original position, now projecting 8". Add rough mound of stone around base.
Burned, sawn, rotted, 48"x4 ft. sugar pine stump N.30°W., 15.2 ft. double scars add BT tag.
Sawn, fallen, out of position slid down hill 15'± 22"x7 ft. D.Fir fully healed blaze with BT tag N.23°E., 24.0 ft.

continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New - Sawn 28"x4½ ft. D.Fir stump S.40°W., 44.8 ft. all scribing visible on unhealed blaze, has BT tag.
7"D.Fir S.87°E., 20.5 ft. scribed T24S R1W S17 BT on double blaze, 3½" mag nail right side center.
4" D.Fir S.59°W., 4.6 ft. scribed X BT on double blaze add 3½" mag nail right side center.
Note - Compass decl. 14¼°E.
The WGS 84 Lat/long is: N43°29'16.19", W122°50'24.41"

Fd. BC & BTs 2/2025 - by D. Saily - M184-56