

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2856-7)

Set a hemlock post, 3½ ft. long, 3" sq., 224" in the ground, for ¼ sec. cor. marked ¼ S on W face, from which

A fir, 24" dia., bears S.52°E., 29 lks., mkd: ¼ S BT.

A fir, 30" dia., bears S.64°W., 8 lks., mkd: ¼ S BT.

This cor. is on a hillside sloping E about 50 ft. above last spur.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - April 1970 - C.S. File 54/27-183

Found - Orig. 24" now 30" Fir, alive, S.52°E., 19.1 ft., shows good scar, we tag.

Orig. 30" now 36" Fir alive, S.64°W., 5.3 ft. open & find "BT" scribe.

Set - Brass cap at cor. mkd: County Surveyors T24S R1W Office 1970 ¼ S 7|S 8

New BT - 10" Hemlock N.22°W., 8.6 ft. mkd: "¼ S7 CS BT"

This corner lies about ¼ mile S of paved access road that runs along the Calapooya Divide.