

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2857)

Set a pine post, 4 ft. long, 4" sq. 24" in the ground for cor. of secs. 5, 8, 7, & 6, marked T24S S5 on NE, R1W S8 on SE, S7 on SW, & S6 on NW faces, with 5 notches on S & E edges, from which

- A fir, 10" dia., bears N.58°E., 4 lks. mkd: T24S R1W S5 BT
- A fir, 6" dia., bears S.12°E., 29 lks. mkd: T24S R1W S8 BT
- A fir, 6" dia., bears S.30°W., 26 lks. mkd: T24S R1W S7 BT
- A fir, 6" dia., bears N.40°W., 7 lks., mkd: T24S R1W S6 BT

This cor. is on a hillside, sloping E about 125 ft. below wagon road.

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor & Rollin D. Aanrud, Surveying Tech, under group # 533, surveyed Oct. 1963 - (DCSO records Vol. 31 Page(s) 13144-5)

The cor. of secs. 5, 6, 7, & 8, determined at rec. bearing & dist. from the orig. BTs:

- A fir, 15" dia., bears N.50½°E., 4 lks., with scribe marks BT visible on opened blaze. (Rec. bearing N.58°E.)
- A fir snag, 9" dia., bears S.12°E., 29 lks., with scribe marks T24S R1W S8 BT visible on partially healed blaze.
- A fir, 10" dia., bears S.30°W., 26 lks., with scribe marks W S visible on partially healed blaze.
- A fir, 8" dia., bears N.40°W., 7 lks., with scribe marks T24S R1W S6 visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked:

T24S	R1W
<u>S 6</u>	<u>S 5</u>
S 7	S 8
1963	

from which the new BTs

- A fir, 13" dia. bears N.62°E., 42 lks. mkd: T24S R1W S5 BT
- A fir, 10" dia. bears S.65°E., 32 lks. mkd: T24S R1W S8 BT
- A fir, 11" dia. bears S.31°W., 30 lks. mkd: T24S R1W S7 BT
- A fir, 16" dia. bears N.64°W., 20 lks. mkd: T24S R1W S6 BT

Nick Juliano, Triangle Eng. - For: Weyerhaeuser Co. - Oct. 1976 - M 62-35

 Found - 2" IP with a 1963 BLM brass cap.
 18" Fir, N.58°E., 2.6 ft., scribe visible. (Rec. 15" N.50½°E.)
 8" Fir snag, S.10°E., 18.3 ft. scribe visible. (Rec. 9" S.12°E., 29 lks.) continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" Fir S.30°W., 15.6 ft., scribe visible. (Rec. 26 lks.)
10" Fir, S.33°W., 17.9 ft., scribe visible (Rec. 11" S.31°W., 30 lks.)
18" Fir, N.62°W., 12.9 ft., scribe visible (Rec. 18" N.40°W., 7 lks.)
6" Fir snag, N.33°W., 4.5 ft. scribe visible (Rec. 8", N.40°W., 7 lks.)
Did not renew.