TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2845)

Set a chincapin post, 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N face, from which
A cedar, 10" dia., bears N.3°W., 29 lks., mkd: ¼ S BT.
A fir, 14" dia., bears S.65°E., 15 lks., mkd: ¼ S BT.
This cor. is on a hillside, sloping S about 75 ft. below dry creek bed.

Howard Johnstone - Roseburg Lumber Co. - 3/31/1977 - M 65-15

Set - 5/8"x40" iron rod & alum. cap.
12" Cedar bears N.3°W., 19.1 ft. OBT
27" Fir bears S.65°E., 9.9 ft. OBT

BLM Dependent resurvey by James E. Jelley & Wayne L. Rogers, Cadastral Surveyors under Group #1051 surveyed April 1981/Sept. 1982 - (DCSO records Vol. 45 Page(s) 17336)

The ¼ sec. cor. of secs. 20 & 29, perpetuated & recorded by Johnstone in 1977, monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above ground, with alum. cap mkd:

$$\text{¼}\ \frac{20}{29}$$

from which the orig. BTs
A fir, 24" dia., bears S.65°E., 15 lks., with healed double blaze.
A cedar, 17" dia., bears N.3°W., 29 lks., with fragmentary scribe marks visible on partially healed double blaze.