

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Pages 2849-50)

Set a cedar post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on N face, from which
 A madrona, 6" dia., bears N.50°E., 16 lks., mkd: 1/4 S BT.
 A madrona, 12" dia., bears S.22°W., 41 lks., mkd: 1/4 S BT.
This cor. is on a steep hillside, sloping W about 100 ft. below ridge.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Clete Putnam - June 29, 1962 - C.S. File 52/42-18

Found - Madrone, now 12" N.50°E., 10.6 ft. Chopped open & fd. good scribing "S"
 22" D.Fir not a madrone, S.22°W., 27.1 ft. shows 2 very plain old scars. Reblaze & scribe this tree "1/4 S20 CS BT"
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W S17 OFFICE 1962 1/4 S20
New BT - 6" D.Fir N.8 1/2°E., 15.6 ft. mkd: 1/4 S17 CS BT.

Fd. & used on BLM Dependent resurvey by James E. Jelley & Wayne Rogers, Cadastral Surveyors under Group #1051 surveyed April 1981/Sept 1982 - (DCSO rec Vol 45 Pgs 17343-4)

Dan Saily, Lone Rock Timber - Crew: Brett Ragon, Brodie Minter & Trevor Clemo - 2/2025 - M184-56

Found - 2 1/2" DCSO brass cap and iron pipe (properly mkd)
 12" D.Fir bears N.8 1/4°E., 15.6', 1981 rec. N.8 1/2°E., 15.51' 23 1/2 lks) with a healed face. We tag.
 24"x6' tall D.Fir stump bears S.21 3/4°W., 25.9', 1981 BLM rec. S.22°W., 27.06' (41 lks), with a healed face and BLM tag.
New - 8" D.Fir bears S.9°E., 41.7'. We scribe 1/4 S20 BT and tag.
 12" D.Fir bears N.71 1/4°W., 18.5'. We scribe 1/4 S17 X BT and tag.
 18" D.Fir bears S.35°W., 14.5'. We scribe 1/4 S20 BT and tag.
Corner monument lies on steep west facing slope in mixed age timber stand approximately 250' east of a creek running N-S. Top of monument is 1.1' above ground level. We place a 5 1/2' tall galvanized, steel U-post 1.0' north.
BTs were scribed at root crown with dists measured to an alum. nail at side center