



TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

38" Fir, S.81°W., 104.5 ft. to W. Co. nail W. Co. R.P.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause;  
Oct. 30, 1996 - C.S. File 65/9-25

-----  
Found - 3¼" dia. brass cap on a 2½" O.D. iron pipe, protrudes 4" above ground (1963 B.L.M.)  
20x8x8" stone, marked "¼" is fd on top of ground along southeasterly side of BC/IP (orig. stone)  
20" now 26" dia. 5½ ft. high D.Fir stump with a healed blaze, bears S.26°W., 13.1 ft. (brg. agrees with renewal record. Dist. is to center of root crown, original dist. 12.5 ft. would fit well with a face measurement) O.B.T.  
20" now 35" dia. 2 ft. high D.Fir stump with a healed blaze, bears N.50°E., 31.0 ft. (bearing agrees with DCS0 renewal rec; dist agrees w/orig. rec) O.B.T.  
42" now 42" dia. 3 ft. high D.Fir stump with Weyerhaeuser Co. "W" nail on east side of trunk, center of stump bears S.80°W., 104.5 ft. (rec. going to nail is S.81°W., 104.5 ft., bearing should be S.79°W., possibly read wrong side of compass, distance is good) 6/76 Weyerhaeuser Co.  
42" now 42" dia. D.Fir with Weyerhaeuser Co. "W" nail on south side of trunk, center of tree bears N.21°W., 98.2 ft. (rec. going to nail is N.19°W., 96.4 ft. possibly read wrong side of compass, dist. is good) 6/76 Weyerhaeuser New Accessories -  
10" dia. Chinquapin, double blazed and scribed "¼ S5 CS BT" bears N.32°E., 6.3 ft.  
5" dia. Pine, double blazed and scribed "¼ S8 CS BT" bears S.58½°W., 37.2 ft. to center of root crown.  
9" dia. Hemlock, double blazed and scribed "¼ S8 CS BT" bears S.13°W., 25.9 ft. to center of straight trunk at upper blaze. Note: Tree is a pistol butt.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 7/14/2020 (filed 11/3/2022) - C.S. File 67/54-42

-----  
Reported as Fd OK