

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2833)

-----  
Set a hemlock post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 9, 16, 17, & 8, marked T24S S9 on NE, R1W S16 on SE, S17 on SW, S8 on NW faces, with 4 notches on E & S edges; from which

A hemlock, 14" dia., bears N.38°E., 6 lks., mkd: T24S R1W S9 BT

A fir, 6" dia. bears S.60½°E. 29 lks. mkd: T24S R1W S16 BT

A fir, 6" dia. bears S.24°W., 26 lks. mkd: T24S R1W S17 BT

A fir, 6" dia. bears N.58°W., 22 lks., mkd: T24S R1W S8 BT

This cor. is on a steep hillside, sloping N about 300 ft. below spur last noted.

Howard Johnstone, LS 498 - For: Roseburg Lumber - May 1980 - M 83-62

-----  
Found - 1/2" iron pipe in rock mound (unrecorded)  
Orig. 14" dia., Hemlock, now 30" dia., bears N.38°E., 4.0 ft.

Orig. 6" dia., Fir, now 18" dia., bears S.60°E., 19.1 ft.

Orig. 6" dia., Fir, now 8" stump bears S.24°W., 17.2 ft.

Orig. 6" dia., Fir, now 20" dia., bears N.58°W., 14.5 ft.

Set - 5/8" x 30" iron rod & alum. cap.