

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2835)

Set post, 4 ft. long, & 4" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 S on W face, from which:

A pine, 20" dia., bears N.63°E., 18 lks., mkd: 1/4 S BT.

A fir, 12" dia., bears S.64°W., 48 lks., mkd: 1/4 S BT.

This cor. is on a hillside, sloping S about 25 ft. above Creek.

Nick Juliano, Triangel Engineering - For: Weyerhaeuser Co. - Oct. 1976 - M 62-35

Set - 3/4" iron pipe from orig. BTs by distance only:

20" now 22" W.Pine bears N.46°E., (rec. N.63°E.) 11.0 ft. to head of RR spike, orig. BT.

12" now 22" Fir, S.70°W., (rec. S.64°W.) 30.6 ft. (rec. 48') to head of RR spike, orig. BT.