

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2836)

Set a fir post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 4, 9, 8, & 5, marked T24S S4 on NE, R1W S9 on SE, S8 on SW, S5 on NW faces, with 4 notches on E & 5 notches on S edges; from which

A fir, 16" dia. bears N.60°E., 68 lks, mkd: T24S R1W S4 BT

A fir, 16" dia. bears S.56½°E. 93 lks. mkd: T24S R1W S9 BT

A cedar, 30" dia., bears S.43°W., 14 lks., mkd: T24S R1W S8 BT.

A fir, 14" dia. bears N.53°W. 117 lks. mkd: T24S R1W S5 BT
This cor. is on a hillside, sloping S about 50 ft. above creek.

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor & Rollin D. Aanrud, Surveying Tech, under group # 533, surveyed Oct. 1963 - (DCSO records Vol. 31 Page(s) 13142-3)

The cor. of secs. 4, 5, 8, & 9, determined at rec. bearing & dist. from the orig. BTs:

A fir, 30" dia., bears N.60°E., 68 lks. with healed blaze.

A fir, 25" dia., bears S.56½°E., 93 lks., with scribe marks T24S R1W S9 BT visible on partially healed blaze.

A cedar, 30" dia., bears S.43°W., 14 lks., with healed blaze.

A sugar pine, 37" dia., bears N.53°W., 117 lks., with healed blaze. (Rec. calls for a fir)

At the corner point

Set an iron post, 28" long, 2½" dia., 18" in the ground, to solid rock, & in a mound of stone, 3 ft. base, to top, with brass cap marked:

T24S R1W

S 5 | S 6

S 8 | S 9

1963