

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2838)

Set a basalt stone 16x12x12" 12" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 24" dia., bears N.86½°E., 120 lks., mkd: ¼ S BT.

A fir, 36" dia., bears N.15°W., 22 lks., mkd: ¼ S BT.

This cor. is on a steep hillside, sloping SE about 20 ft. below trail.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - April 1970 - C.S. File 54/27-214

Found - Corner stone, as called for, in place.

Orig. 24" now 32" Fir, alive, N.86½°E., 79.2 ft., shows good scar, we tag.

Orig. 36" now 40" Fir, alive, N.15°W., 14.5 ft., shows good scar, we tag.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W (reset old stone alongside) OFFICE 1971 ¼ S5|S 4

We do not mark new BTs as orig. BTs are in good condition & the only trees available are of the same size.

Corner lies 100 ft S of old Bohemia Jeep Trail not drive able

Fd. Ok DCSO VRT, 7/25/1973 - C.S. File 56/34-6 Pg2