

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2831-2)

-----  
Set a basalt stone 12x8x8" 8" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which

A pine, 6" dia., bears N.42°E., 50 lks., mkd: 1/4 S BT.

A fir, 54" dia., bears S.21°E., 13 lks., mkd: 1/4 S BT.

This cor. is on a hillside, sloping SE about 200 ft. above creek.

-----  
Douglas Co. Surveyors Office - James Byron, County Surveyor - V. Perron - Aug. 14, 1970 - C.S. File 54/27-198

-----  
Found - Orig. 45" now 54" Fir, S.21°E., 8.6 ft., shows good scar. We do not open.

Orig. 6" now 18" down Pine, we open & find good scribing N.42°E., 33.0 ft.

Rock out of ground, which checks record size, no marks found. Near corner.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W

OFFICE 1/4 S 16  
1970 S 21

New BT - 12" Hemlock bears S.84°E., 38.0 ft. scribed: 1/4 S21 CS BT

24" D.Fir bears N.4°E. 49.0 ft. scribed: 1/4 S16 CS BT

-----  
Douglas Co. Surveyors Office - Karen Reed - Pete Earle - Frank Silagy - Oct. 15, 1979 - C.S. File 60/34-19

-----  
Found - A basalt stone 12"x8"x8" with no marks at approx. cor. location.

1"x36" I. Pipe with brass cap marked County Surveyor Office 1/4 T24S S16 S21 R1W 1970, lying on the ground near cor.

Orig. 54" dia., Fir, now a 45" dia., 3 ft. high stump bears S.21°E., 8.6 ft., shows a good scar & has been capped.

Orig. 6" Pine now 17" & down, root hole bears N.42°E., 33.0 ft., partially opened blaze reveals "BT"

12" Hemlock, now 14" with visible scribing "4 S21 CS BT" in double blaze bears S.84°E., 37.5 ft. (Rec. 38.0 ft.)

24" Fir, now 26" 4 ft. high stump with visible scribing "1/4 S16 CS BT" in a partially healed double blaze, bears N.3°E., 49.0 ft. (Rec. N.4°E.)

continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set - Reset 1"x36" I. Pipe with brass cap at rec. bearing  
& dist. from orig. stump (S.21°E., 8.6 ft.) &  
mark "Reset 1979" on cap. Place stone north side  
of cap.  
New - 48" sugar pine scribed "¼ S21 CS BT" in a double  
blaze bears S.86°W., 115.1 ft.  
Set boat spike on northerly side of tree marked  
"DCSO" measurement taken to BS, also center of  
tree.  
Corner on east slope of spur in clearcut.