

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2812)

-----  
Falls on a boulder, 10x8x3 ft. above ground. At exact point for 1/4 sec. cor. I mark a cross & 1/4 on W side from which  
A fir, 30" dia., bears N.28°E., 32 lks., mkd: 1/4 S BT.  
A chincapin, 6" dia., bears S.63°W., 28 lks., mkd: 1/4 S BT.  
This cor. is about 175 ft. above creek.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - July/Aug. 1962 - C.S. File 52/42-22

-----  
Found - Faint "X" on rock outcrop, 3'x8'x10' above ground.  
Did not find "1/4" on W face.  
D.Fir now 40" N.28°E., 21.1 ft., slope dist. Tree shows very plain axe scar. Did not open - (level dist. 19.6 ft.)  
No trace fd. of SE BT.  
New - I deepen cross on rock outcrop (cross is on S edge of Rock about 2 ft. East of SW cor. of top of rock)  
23" Sugar Pine, N.30°W., 10.6 ft., mkd: 1/4 S33 CS BT.