

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2814)

Falls on a boulder, 6x6x6 ft. above ground. At the exact point for the ¼ sec. cor., I mark a cross, & ¼ on W face of boulder, from which

A fir, 60" dia., bears N.40°E., 30 lks., mkd: ¼ S BT.

A chincapin, 6" dia., bears S.55°W., 27 lks., mkd: ¼ S BT.
This cor. is about 25 ft. below spur.

Thomas E. Shrum - For: U.S. Plywood - 6/1967 - M36-13 and
Thomas E. Shrum - For: Menasha Corp. - 1970 - M 50-44

Found orig. stone, Fir 60", N.40°E., 30.0'

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy -
John Powell - Sept. 30, 1983 - C.S. File 62/9-5

Found - 1"x1" chiseled "+" & "¼" on top of a boulder 18'x6'x6' above ground. Orig. notes call chiseled "+ ¼" on west face of boulder 6'x6'x6' above ground.

Orig. 60" fir with well healed blaze bears N.40°E., 19.8 ft. (M50-44 shows 30 ft. This probably mistaken for 30 lks., per orig.)

Orig. 6" chinquapin not found.

New - 12" fir double blazed & scribed "¼ S27 CS BT" bears S.58½°E., 17.7 ft.

Set a 1/2"x8" spike in top of an 18" hemlock stump, bears N.73½°W., 39.1 ft. Spike set through a Douglas County Surveyors Office BT tag.

Set a 1/2"x8" spike in top of an 20" hemlock stump, bears S.41½°W., 60.3 ft. Spike set through a Douglas County Surveyors Office BT tag.

Note - Corner is on a North slope in a N-S cutting line, clear cut to the west.