

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2815)

Set a chincapin post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 22, 27, 28, & 21, marked T24S S22 on NE, R1W S27 on SE, S28 on SW, S21 on NW faces, with 2 notches on S & 3 notches on E edges; from which

- A pine, 18" dia., bears N.18°E., 54 lks., mkd: T24S R1W S22 BT.
- A fir, 6" dia., bears S.43°E., 19 lks., mkd: T24S R1W S27 BT.
- A pine, 16" dia., bears S.23°W., 53 lks., mkd: T24S R1W S28 BT.
- A pine, 24" dia., bears N.53°W., 82 lks., mkd: T24S R1W S21 BT.

This cor. is on a steep hillside, sloping NW about 50 ft. below creek last noted.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Terry Connell - May 1966 - C.S. File 52/42-40

Found - Orig. 18" now 32" Pine N.18°E., 35.6 ft. Alive & in good condition.
 Orig. 6" now 12" Fir S.43°E., 12.5 ft. Alive & in good condition.
 Orig. 16" now 20" Pine S.23°W., 35.0 ft. Alive & in good condition.
 Orig. 24" now 36" Pine N.53°W., 54.1 ft. Alive & in good condition.

Set - Brass cap mkd: COUNTY SURVEYORS T24S R1W S 21 | S 22
 OFFICE 1966 S 28 | S 27

Note - Since all BTs are OK. We do not mark new ones.
 Corner lies on easterly slope of spur ridge, sloping N. approx. 60 ft. off top of ridge.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - John Powell - Janet Lundeen - Sept. 1983 - C.S. File 62/9-3

Found - 1966 county brass cap on iron pipe firmly set protruding about 14" above ground, properly mkd. Orig. post not found.
 An 18" pine, now a 30" stump with well healed blaze bears N.20°E., 35.1 ft. (Rec. N.18°E., 35.6 ft.)
 6" fir, now 11", (badly bowed with double top) has well healed double blaze with an "X" above upper blaze, bears S.42°E., (Rec. S.43°E., 12.5 ft. to center of trunk at X blaze. Root crown bears S.20°E., 12.8 ft. continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

16" pine now 30" dia., stump with well healed blaze bears S.25°W., 32.2 ft. (Rec. S.23°W. 35.0 ft)
Pine 24" now 36" dia., with well healed blaze bears N.53°W., 54.9 ft. (Rec. 54.1 ft.)
New BTs- Hemlock 8" dia., double blazed & scribed "T24S R1W S22 CS BT" bears N.12½°E., 48.7 ft.
Hemlock 10" dia., double blazed & scribed "T24S R1W S28 CS BT" bears S.20°W., 4.1 ft.
Note - Corner lies on NNE slope approx. 55 ft. east of a spur ridge running northerly. Cutting lines run N-S-E & W, clear cut of NE & SW.