TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2817-8)

Set a basalt stone 14x8x6" 11" in the ground for cor. of secs. 15, 22, 21, & 16, marked with 3 notches on S & E edges, from which

A hemlock, 6" dia., bears N.22°E., 27 lks., mkd: T24S R1W S15 BT.
A fir, 42" dia. bears S.62°E. 57 lks. mkd: T24S R1W S22 BT
A fir, 48" dia. bears S.84°W. 63 lks. mkd: T24S R1W S21 BT
A fir, 30" dia. bears N.56°W. 38 lks. mkd: T24S R1W S16 BT

This cor. is on a steep hillside, sloping SW about 150 ft. above creek last noted.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy; M. Stone, crew - Aug. 1962 - C.S. File 52/42-24

Found - Rock 14x8x6" with notches as called for, tipped over & downhill about 2 ft. from corner.
42" Fir snag S.62°E., 37.6 ft. (slope dist.) scribing visible on old face, not grown over, "T24S R1W S21 BT"
Hemlock, down & rotten, but stump part in position, N.22°E., 17.8 ft.
Fir, uprooted & down, bears S.84°W., approx. 55 ft. (slope dist.) (Notes call for tree S.84°W., 41.6 ft.) No scars vis. on this tree.
60" Fir, uprooted & down, showing very plain axe scar approx. S.10°E., 41 OR 42 ft. (not called for in notes)

Set - Brass cap alongside rock & mkd:

COUNTY SURVEYORS
OFFICE 1962

T24S	R1W
S 16	S 15
S 21	S 22

New BTs- 11" I.Cedar N.18°W. 38.3 ft. mkd: T24S R1W S16 CS BT
48" D.Fir N.84°E., 25.2 ft. mkd: T24S R1W S15 CS BT
34" D.Fir S.52°W., 51.4 ft. mkd: T24S R1W S21 CS BT
7" Chinquapin S.40°E. 14.8 ft mkd: T24S R1W S22 CSBT