

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2819)

Falls on a boulder, 3x3x2 ft. above ground. At exact point for 1/4 sec. cor. of E side. I mark a cross & 1/4 from which
A fir, 16" dia., bears S.38°E., 32 lks., mkd: 1/4 S BT.
A fir, 24" dia., bears N.67°W., 9 lks., mkd: 1/4 S BT.
This cor. is about 25 ft. below dry bed of creek.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Terry Connell - May 1966 - C.S. File 52/42-41

Found - 3'x3'x2' boulder at corner, failed to find marks on E face.
Orig. 16" now 20" Fir S.38°E., 21.1 ft. Open & shows "1/4S BT" now snag.
Orig. 24" now 30" Fir N.67°W., 5.9 ft., alive, shows good scar, we do not open.
Set - Brass cap mkd: COUNTY SURVEYORS OFFICE 1966 T24S R1W S16|S15
New BT - 14" D.Fir N.74°E., 26.6 ft. mkd: 1/4 S15 CS BT
Note - Brass cap is against East face of boulder set in a mound of stone. Corner lies on steep east slope.

Fd. Ok T. Shrum, 11/1980 - M84-55

Douglas Co. Surveyors Office - Stephen J. Flause - Terrie Franssen - July 22, 1990 - C.S. File 64/10-1

Found - 3x3x2 ft tall boulder East side spalled. No marks fd 3/8 OD by 36" iron pipe with a 2 1/2" 1966 county brass cap mkd. as in 1966 ren. is fd. loose from ground & in scattered rock mound on east edge of boulder.
2 orig. BTs fd: meas. to east side of boulder near north end.
A Fir, 16" dia., now a 21" DBH 40 ft. tall D.Fir snag with a previously opened double blaze with the scribing "1/4S BT" visible bears S.38°E., 20.0 ft. dist. (rec. S.38°E., 21.1 ft.; this is a slope dist.)
A Fir, 24" dia., now a 30" DBH D.Fir with a fully healed double blaze bears N.67°W., 5.4 ft. (Rec N.67°W., 5.9 ft. this is a slope dist.)
A 14" D.Fir now a 14" DBH D.Fir bears N.78 1/2°E., 23.5 ft. (Rec. N.74°E., 26.6 ft., this bearing is to near vertical sec. of trunk, not root crown, & dist. is a slope dist.)

continued next page

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - Point described above near North end of boulder & on most easterly side agrees well with orig. bearings & all slope distances agree to this position. The brass cap mon. is positioned directly along the east edge of boulder & partially under overhang of said boulder. The BC position is the same as the above mentioned measurement to position on the boulder. The marks "RESET 1990" are added to the brass cap. A mound of stone approx. 32x14x17" tall is piled on east edge of BC. Monument is flush with top of stone mound.

New BTs- 4" DBH hemlock scribed "X BT" on a double blaze bears N.42°E., 27.7 ft.

10" DBH Limber Pine scribed "¼ S16 CS BT" on a double blaze bears N.9¼°W., 35.5 ft.

Corner lies on steep east slope approx. 200 ft. SW'ly from ridge back trail running north-easterly.