

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T23-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 5 Page(s) 2137)

-----  
Set basalt stone 20x20x12 ins., 15" in the ground, for cor. to secs. 3, 4, 33 and 34, marked with 3 notches on the E. & W. edges, from which  
A Fir 30" dia., bears N.38°E., 21 lks. dist. mkd. T23S R1W S34 BT.  
A Fir 30" dia., bears S.27°E., 94 lks. dist. mkd. T24S R1W S3 BT.  
A Fir 30" dia., bears S.8°W., 30 lks. dist. mkd. T24S R1W S4 BT.  
A Fir 30" dia., bears N.2°W., 35 lks. dist. mkd. T24S R1W S33 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April 16, 1970 - C.S. File 54/27-202

-----  
Found - No trace of corner stone.  
Orig. 30" Fir, now decayed stump, N.38°E., 13.9 ft. with scribe visible.  
Orig. 30" now 34" Fir, alive, S.27°E., 62.0 ft., shows good scar, we tag.  
Orig. 30" now 34" Fir, alive, S.8°W., 23.1 ft. (Rec. 19.8 ft.) good scar, we tag.  
Orig. 30" now 35" Fir, alive, N.2°W., 19.8 ft. (Rec. 23.1 ft.) opened, scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T23S R1W S 33 | S 34  
T24S S 4 | S 3  
1970

New BTs- 6" D.Fir N.52°E., 21.4 ft. mkd. "S34 CS BT".  
13" D.Fir N.62°W., 22.3 ft. mkd. "T23S R1W S33 CS BT"

Corner lies on very steep, southerly slope approx. 50 ft. from S. edge of logging access road.

Fd. OK, July 1973, V.R.Tracy, DCS0 - C.S. File 56/34-6 Pg2