

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T25-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2780-81)

Set a Yew post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
A Fir 24" dia., bears N.50°E., 43 lks. dist. mkd. ¼ S BT
A Fir 36" dia., bears S.42°W., 35 lks. dist. mkd. ¼ S BT
Cor. is on a hillside, sloping S. about 75 ft. above creek last noted.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Nov. 3, 1966 - C.S. File 52/30-56

Found - Orig. 24" now 36" Fir, N.50°E., 28.3 ft. open and find "B" scribe.
Orig. 42" now 48" Fir, S.42°W., 23.1 ft., alive, shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T24S R1W ¼ $\frac{S\ 34}{S\ 3}$
T25S
1966

New BTs- 12" Hemlock N.31°W., 9.2 ft. mkd. ¼ S34 CS BT.
8" Hemlock S.2°W., 3.3 ft. mkd. ¼ S3 CS BT.
Corner lies N. of Grizzly Creek approx. 250 ft. on bench.