

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2816)  
-----  
Set a basalt stone 16x10x10" 11" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which  
    A fir, 6" dia., bears N.27°E., 8 lks., mkd: 1/4 S BT.  
    A fir, 10" dia., bears S.27°E., 21 lks., mkd: 1/4 S BT.  
This cor. is on a steep hillside, sloping E 25 ft. above last creek.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - April 14, 1970 - C.S. File 54/27-212  
-----  
Found - Corner stone mkd: "1/4" at 1/4 corner.  
    Orig. 6" now 7" Fir, 10 ft. high snag, N.27°E., 5.3 ft., prev. opened & shows "BT" scribe. we open higher & find "1/4S" scribe.  
    Orig. BT to SE Gone.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W  
    (Reset stone OFFICE 1/4 S 22  
    alongside) 1970 S 27  
New BTs- 10" D.Fir S.45°W., 14.5 ft., mkd: "1/4 S27 CS BT"  
    8" Cedar N.55°W., 8.1 ft., mkd: "1/4 S22 CS BT"  
This corner lies on steep, east slope about 50 ft. from creek, course NE