

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2798)

Set a basalt stone 12x10x10" 9" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 36" dia., bears S.78°E., 15 lks., mkd: ¼ S BT.

A fir, 10" dia., bears N.53°W., 36 lks., mkd: ¼ S BT.

This cor. is on a steep hillside sloping SW about 150 ft. above creek.

Douglas Co. Surveyors Office - R.B. Kimberling - P.L. Earle - July 25, 1977 - C.S. File 59/38-6

Found - 36" Fir now 40" bears S.78°E., 9.9 ft., with well healed double blaze.

10" Fir now 19" bears N.53°E., 23.8 ft., with well healed double blaze. We opened upper blaze & found scribe mark "S"

Set - 1"x36" iron pipe with brass cap 6" above ground mkd:
COUNTY SURVEYORS OFFICE 1977

T 24 S
COR
S 34 S 35
R 1 W

Note - Corner is at NE cor. of clearcut unit.