

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor Secs 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2801-2)

Set a basalt stone, 16x12x10" 12" in the ground, for cor. of secs. 23, 26, 27, & 22, marked with 2 notches on S & E edges, from which

A fir, 6" dia. bears N.65°E., 65 lks. mkd: T24S R1W S23 BT

A pine, 12" dia., bears S.60°E., 14 lks., mkd: T24S R1W S26 BT.

A pine, 16" dia., bears S.67°W., 58 lks., mkd: T24S R1W S27 BT.

A fir, 12" dia. bears N.47°W. 81 lks. mkd: T24S R1W S22 BT

This cor. is on topo of spur, sloping W about 25 ft. above creek, last noted.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Clete Putnam - Oct. 1961 - C.S. File 52/42-14

Found - Rock as called for in Gov't notes.

23" Pine S.67°W., 38.3 ft., opened previously, good scribing visible "T24S R1W S27 BT"

18" Fir N.47°W., 53.5 ft., shows good scar.

22" Pine S.60°E., 9.2 ft., shows good scar.

12" Fir N.65°E., 4.3 ft., instead of 42.9 ft., shows good scars.

Alongside rock set brass cap mkd: County Surveyors S 22|S 23
Office 1961 T24S R1W S 27|S 26

New BT - 18" Pine S.77°W., 34.4 ft., mkd: T24S R1W S27 CS BT

All old BTs in good condition except Pine in SW Quad