

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2803)

Set a basalt stone 14x10x10" 10" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 24" dia., bears S.84°E., 75 lks., mkd: ¼ S BT.

A fir, 42" dia., bears N.53°W., 66 lks., mkd: ¼ S BT.

This cor. is on a steep hillside, sloping S about 250 ft. above creek.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - April 13, 1970 - C.S. File 54/27-210

Found - Corner stone, in place, mkd: ¼
Orig. 24" now 30" D.Fir, alive, S.84°E., 49.5 ft., shows good axe scar, tagged.
Orig. 42" now 46" D.Fir alive, N.53°W., 43.6 ft., shows good axe scar, we tag.

Set - Brass cap at cor. mkd: County Surveyors T24S R1W
(Set old corner Office 1970 ¼ S 22|S 23 stone alongside)

New BTs- 8" Hemlock S.35°W., 27.9 ft., mkd: "¼ S22 CS BT"

14" D.Fir S.81°E., 24.8 ft., mkd: "¼ S23 CS BT"

This corner lies on moderate S slope near foot of very steep, ascent to N.