

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor Secs 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2804)

Set a basalt stone, 12x12x12", 9" in the ground, for cor. of secs. 14, 23, 22, & 15, marked with 3 notches on S & 2 notches on E edges; from which

A fir, 16" dia. bears N.19°E. 45 lks. mkd: T24S R1W S14 BT

A fir, 30" dia., bears S.56½°E., 44 lks., mkd: T24S R1W S23 BT.

A pine, 36" dia., bears N.35°W., 16 lks., mkd: T24S R1W S22 BT.

A fir, 30" dia. bears N.48°W. 33 lks. mkd: T24S R1W S15 BT

This cor. is on a steep hillside, sloping SE about 25 ft. above dry creek bed, last noted.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Clete Putnam - Oct. 1961 - C.S. File 52/42-15

Found - Dead Pine, now 40", S.35°W., 10.6 ft., previously opened, good scribing visible.

22" Fir N.19°E., 29.7 ft., shows 2 good scars. Did not open.

34" Fir S.56½°E., 29.0 ft., shows good scar. Did not open.

36" Fir N.48°W., 21.8 ft., shows good scar. Did not open.

Did not find rock at corner as called for.

Note - Pine is S.35°W., instead of N.35°W., as called for in Gov't notes.

Set - Brass cap mkd: County Surveyors T24S R1W S 15|S 14
Office 1961 S 22|S 23

Three of orig. BTs in good condition.

New BTs- 25" D.Fir S.78°W., 43.1 ft., mkd: T24S R1W S22 CS BT