

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCS0 recs Vol. 7 Page(s) 2806)

Set a basalt stone 16x12x10" 12" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 30" dia., bears S.41°E., 26 lks., mkd: ¼ S BT.

A chincapin, 6" dia., bears N.19°W., 17 lks., mkd: ¼ S BT.
This cor. is on a steep hillside, sloping SW bout 175 ft. above creek.

Douglas Co. Surveyors Office - Gary Langlitz, Deputy - Pete Earle - Clell Goodwin - June 17, 1974 - C.S. File 56/51-22

Found - Stone, 16x12x10", loosely set, with a faint "¼" chiseled on a face, pointing generally west.
30" now 32" D.Fir showing a good scar. Since it appears that the orig. stone has been disturbed, we open the BT find good scribing.

At the corner point as determined at rec. bearing & dist. from the only remaining BT, a 30" now 32" D.Fir bearing S.41°E., 17.2 ft. we set a brass cap, flush with the ground

mkd: COUNTY SURVEYORS T 24 S
OFFICE S 15 | S 14
1974 ¼
R 1 W

We place basalt corner stone alongside brass cap & mark the following BT:

8" Chinquapin bears N.1½°W. 32.7 ft. scribed "¼" S15 CS BT

16" Hemlock bears N.78½°W., 72.3 ft., scribed "¼" S15 CS BT