

PRIMARY CORNER DESCRIPTION Cor Secs 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2806)

Set a basalt stone, 12x10x10", 9" in the ground, for cor. of secs. 11, 14, 15, & 10 marked with 4 notches on S & 2 notches on E edge, from which

- A fir, 16" dia. bears N.36°E. 32 lks. mkd: T24S R1W S11 BT
- A fir, 10" dia. bears S.34°E. 27 lks. mkd: T24S R1W S14 BT
- A fir, 24" dia. bears S.2°W. 106 lks. mkd: T24S R1W S15 BT
- A pine, 12" dia., bears N.58½°W., 49 lks., mkd: T24S R1W S10 BT.

This cor. is on a steep hillside, sloping E, about 50 ft. above creek.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 12, 1967 - C.S. File 52/42-59

-
- Found - 16x10x10" corner stone mkd. with 2 notches on N & 4 notches on south, firmly set.
- Orig. 16" now 24" Pine, N.39°E., 21.1 ft., alive, scribe visible on unhealed blaze. (Rec. calls for Fir N.36°E.)
 - Orig. 10" now 13" Fir S.29½°E., 17.8 ft., alive, shows scar. (Rec bearing S.34°E.)
 - Orig. 24" now 31" Fir, S.5°W., 70.0 ft., alive, shows scar. (Rec bearing S.2°W.)
 - Orig. 12" (?) now 24" Pine, N.51°W., 32.3 ft., now snag, scribe visible on unhealed blaze. (Rec bearing N.58½°W.)

Set - Brass cap at cor. mkd: County Surveyors Office T24S R1W S 10 | S 11
 (Reset rock alongside) 1967 S 15 | S 14

- New BTs- 8" Hemlock N.40°W., 16.0 ft. mkd: T24S R1W S10 CS BT
- 7" Hemlock S.54°W., 24.8 ft. mkd: T24S R1W S15 CS BT
- 16" Fir N.49°E., 11.1 ft., mkd: T24S R1W S11 CS BT

Note - This corner lies on steep, easterly slope.