TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2808)

Set a hemlock, post, 4 ft. long, 4" sq. 24" in the ground, for ¼ sec. cor., marked ¼ S on W face, from which
A hemlock, 6" dia., bears N.75½°E., 4 lks., mkd: ¼ S BT.
A hemlock, 10" dia., bears N.43°W., 10 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - V. Tracy - M. Stone - Oct. 1962 - C.S. File 52/42-29

Found - 12" Hemlock N.43°W., 6.6 ft. Has been opened previously, good scribing "¼S BT" visible.
8" dead Hemlock snag, N.75½°E., 2.6 ft., previously opened.
Set - Brass cap at cor. mkd; County Surveyors Office 1962
T24S R1W ¼ S10|S11
New BT - 18" Hemlock S.57°E,. 20.0 ft., mkd: ¼ S11 CS BT (pocket knife scribe)
Corner lies approx. 400 ft. West of E. Pass Creek Rd.