

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2782-83)

 Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for cor. of secs. 36, 1, 2, and 35; marked T24S S36 on NE.; R1W S1 on SE.; T25S S2 on SW.; and S35 on NW. faces; with 5 notches on W. and 1 notch on E. edges, from which
 A Fir 16" dia., bears N.14°E., 24 lks. dist. mkd. T24S R1W S36 BT.
 A Fir 10" dia., bears S.10°E., 20 lks. dist. mkd. T25S R1W S1 BT.
 A Pine 48" dia., bears S.15°W., 21 lks. dist. mkd. T25S R1W S2 BT.
 A Fir 10" dia., bears N.26°W., 31 lks. dist. mkd. T24S R1W S35 BT.
 Cor. is on a hillside, sloping SE. about 50 ft. below spur.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - June 4, 1963 - C.S. 52/30-14

 Found - 11" Fir S.30°E. (not S.10°E.) 13.2 ft., previously opened, good scribing visible T25S R1W S1.
 30" Fir N.14°E., 15.8 ft., shows good scar.
 48" Sugar Pine S.15°W., 13.9 ft., shows good scar.
 15" Fir N.26°W., 20.5 ft., shows good scar.
 Set Brass cap at cor. mkd: County Surveyors Office
 T24S R1W S35|S36
 T25S S 2|S 1
 1963
 New BTs- 21" D.Fir S.55°W., 11.0 ft. mkd. T25S R1W S2 CS BT
 12" I.Cedar N.47°E., 24.1 ft. mkd. T24S R1W S36 CS BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Mike Cline, crew - Aug. 11, 1977 - C.S. File 59/38-14

 Found - 1963 DCSO brass cap and iron pipe, separated and badly bent, below surface of cat trail, properly stamped.
 Orig. Fir 16" now 26" snag, bears N.14°E., 15.8 ft. Tree has well healed blaze.
 10" fir now dead, bears S.30°E., 13.2 ft. (orig. rec. S.10°E.; 1963 renewal rec. S.30°E.) Tree has partially opened blaze scribed T25S R1W S1.
 48" Pine stump bears S.15°W., 13.9 ft. Tree has well healed blaze.

(Cont. Next Page)

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36; 1 & 2, T25-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" now 16" Fir bears N.26°W., 20.5 ft. Tree has well healed blaze.
21" Fir stump bears S.55°W., 11.0 ft. Tree has partially healed blaze scribed "25S R1W S2 CS BT" visible.
An I.Cedar 12" bears N.47°E., 24.1 ft. Tree has open blaze scribed "T24S R1W S36 CS BT".
Set 30" x 1" iron pipe at section corner, 22" deep. Attached brass cap is stamped "Douglas County Surveyor T24S S35 S36 S2 S1 T25S R1W".
No trees to scribe in southerly quadrants.