

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. of Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set a pine post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 25, 26, 35, & 36, marked T24S S25 on NE, R1W S36 on SE, S35 on SW, S26 on NW faces, with 1 notch on S & E edges; from which  
A fir, 6" dia. bears N.18°E., 45 lks. mkd: T24S R1W S25 BT  
A fir, 6" dia. bears S.42°E., 25 lks. mkd: T24S R1W S36 BT  
A fir, 6" dia. bears S.34°W., 57 lks. mkd: T24S R1W S35 BT  
A fir, 48" dia. bears N.64°W. 66 lks. mkd: T24S R1W S26 BT  
This corner is about 40 ft. above McKinley Cr. on a spur, sloping W.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Mike Stone - Nov. 1962 - C.S. File 52/42-31  
-----  
Found - 9" Fir S.34°W., 37.6 ft., previously opened, good scribing visible.  
12" Fir S.42°E., 16.5 ft., shows good scars. Did not open.  
13" Fir N.18°E., 29.7 ft., shows good scars. Did not open.  
60" Fir N.64°W., 56.8 ft., (86 lks. not 66 lks.) shows very plain axe scar.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T24S R1W  
OFFICE 1962 ¼ S 26 | S 25  
S 35 | S 36  
New BTs- 13" W.Pine S.66°W., 17.9 ft., mkd: T24S R1W S35 CS BT.  
8" D.Fir N.30°W., 18.7 ft., mkd: T24S R1W S26 CS BT.  
Corner lies on W. slope, approx. 50 ft. South of top of spur sloping NW.

Fd Ok 5/1970 by VRT, DCSO C.S. File 54/27-186