

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2787)

-----  
Set a basalt stone 12x8x8" 8" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 36" dia., bears East, 9 lks., mkd: ¼ S BT.

A cedar, 12" dia., bears N.30°W., 26 lks., mkd: ¼ S BT.

This cor. is about 40 ft. above McKinley Creek bottom.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Terry Connell - June 1965 - C.S. File 52/42-36

-----  
Found - Basalt stone 8x8x8, firmly set, & mkd. "¼" on W face  
Orig. 36" now 42 Fir, alive & in good cond. East 5.9 ft., shows good scar. We do not open.  
Orig. 12" now 16" Cedar N.30°W., 17.1 ft., open & find "S" scribe.

Set - Brass cap at cor. mkd: County Surveyors Office, 1965  
T24S ¼ S26|S25 R1W

New BTs- 5" D.Fir N.77°W., 12.5 ft., mkd: ¼ S26 CS BT.

Note - We set Rock alongside cap - this corner is on steep East slope.