

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2787-8)

-----  
Set a fir post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 24, 25, 26, & 23, marked T24S S24 on NE, R1W S25 on SE, S26 on SW, S23 on NW faces, with 2 notches on S & 1 notch on E edges; from which

A fir, 24" dia., bears N.45°E., 63 lks., mkd: T24S R1W S24 BT.

A fir, 18" dia., bears S.77°E., 55 lks., mkd: T24S R1W S25 BT.

A fir, 30" dia., bears S.49°W., 108 lks., mkd: T24S R1W S26 BT.

A fir, 24" dia., bears N.62°W., 39 lks., mkd: T24S R1W S23 BT.

This cor. is on a hillside, sloping W, about 100 ft. above ¼ sec. cor.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - May 1970 - C.S. File 54/27-188

-----  
Found - Orig. 18" now 24" Fir, alive, S.77°E., 36.3 ft., shows good scar, we tag.

Orig. 24" now 30" Fir, alive, N.72°W., (rec. N.62°W.) 25.7 ft., shows good scar, we tag.

Orig. 30" now 32" Fir snag, S.45°W., (rec. S.49°W.) 71.3 ft., open & find scribe.

We do not find Fir BT, as described to NE. However, 40" Fir snag bears N.10°E., 50.0 ft., shows good axe scar, we open & find "4" scribe. Looks old enough to be orig.

Set - Brass cap at cor. mkd: County Surveyors Office 1970 T24S R1W S 23 | S 24 S 26 | S 25

New BTs- 10" D.Fir, S.58°W., 30.4 ft. mkd: T24S R1W S26 CS BT  
9" S.Pine, N.5°E., 28.9 ft. mkd: T24S R1W S24 CS BT

This cor. lies on W slope 66.0 ft., W of top of ridge & about 115 ft. N of top of same ridge.