

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2792)

Set a basalt stone 12x8x8" 8" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A fir, 30" dia., bears N.33°E., 88 lks., mkd: ¼ S BT.

A fir, 30" dia., bears N.10°W., 28 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - June 1970 - C.S. File 52/27-194

Found - Corner stone, in place, with only partial chisel marks on W side.

Orig. 36" now 40" Fir alive, N.33°E., 58.1 ft. shows good scars.

Orig. 30" now 38" Fir alive, N.10°W., 18.5 ft. shows good scars.

Set - Brass cap at cor. mkd: County Surveyors T24S R1W (Reset Stone alongside) Office 1970 ¼ S14 S13

New BT - 13" Cedar N.53°E., 23.0 ft., mkd: "¼ S13 CS BT"

This corner lies on very steep, East slope in old growth timber.