TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2792)

Set a basalt stone, 12x8x6", 9" in the ground, for cor. of secs. 12, 13, 14 & 11, marked with 4 notches on S & 1 notch on E edges; from which

A fir, 12" dia. bears N.46°E., 6 lks. mkd: T24S R1W S13 BT
A fir, 14" dia. bears S.75°E. 19 lks. mkd: T24S R1W S13 BT
A fir, 16" dia. bears S.24°W. 17 lks. mkd: T24S R1W S14 BT
A fir, 18" dia. bears N.15°W., 8 lks. mkd: T24S R1W S11 BT

This corner is on a steep hillside sloping NW about 50 ft. below spur last noted.

Thomas W. Coiner, R.S. 413 - For: Bohemia Lumber Co., Inc. - Aug. 24, 1961 - Aug. 24, 1961 - C.S. File 51/209

Point at prop. dist. There is no evidence of the orig. corner

Set - An IP 30x2x6" in the ground, with a mound of stone to top & alum. bronze cap mkd: 11|12 / 14|13 from which:

Andesite boulder 6x5x2.5 ft. above ground bears N.49°E., 24 ft. mkd: X BO T24S R1W S12.

Breccia boulder 5x3.5x3.5 ft. above ground bears N.10°W., 1.0 ft. mkd: X BO T24S R1W S11.

Sugar pine 30" bears S.83°13'E., 282.2 ft. mkd: T24S R1W S14 BT.

D.Fir 32" bears S.8°43'E., 228.8 ft. mkd: T24S R1W S14 BT.

Fd. Ok by V.R. Tracey, DCSO 10/1966 - C.S. file 52/42-48A