

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2794)  
-----  
Set a sandstone 12x10x8" 9" in the ground, for ¼ sec. cor. mkd ¼ on W face, from which  
    A fir, 36" dia., bears N.57°E., 50 lks., mkd: ¼ S BT.  
    A fir, 24" dia., bears N.6°W., 22 lks., mkd: ¼ S BT.

Thomas W. Coiner, R.S. 413 - For: Bohemia Lumber Co., Inc. - Aug. 24, 1961 - Aug. 24, 1961 - C.S. File 51/209  
-----  
Determined from the stump of one of the orig. BTs:  
    A D.Fir stump, 38" bears N.57°E., 33 ft. blaze healed.  
New - D.Fir 26", bears N.52½°E., 106.8 ft. mkd: ¼ S12 BT.  
    D.Fir 28" bears S.5°W., 140 ft. mkd: S11 ¼ BT.  
At the corner point:  
    Set iron pipe 30"x2"x16" in the ground, with mound of stone to top, with alum. bronze cap mkd: ¼ S11|S12

Fd. Ok by V.R. Tracey, DCSO 10/1966 - C.S. file 52/42-48A