

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Dep. Surveyor under contract # 664, dated May 23, 1896 - (DCSO recs Vol. 7 Page(s) 2794-5)

-----  
Set a basalt stone 10x8x8", 7" in the ground, for cor. of secs. 1, 12, 11, & 2, marked with 5 notches on S, and 1 notch on E edges, from which

A fir, 24" dia. bears N.50°E., 73 lks. mkd: T24S R1W S1 BT

A fir, 30" dia. bears S.17°E. 90 lks. mkd: T24S R1W S12 BT

A fir, 10" dia. bears S.31°W. 14 lks. mkd: T24S R1W S11 BT

A fir, 36" dia. bears N.55°W., 39 lks. mkd: T24S R1W S2 BT

This cor. is on a steep hillside sloping W about 25 ft. below spur, last noted.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Joe Brady - Jack Heritage - Aug 1966 - C.S. File 52/42

-----  
Found - 10x8x8" basalt stone with 5 notches on S & 1 notch on E.

Orig. 24", now 26" Fir, N.50°E., 48.2 ft. "BT" scribe on badly rotted stump.

Orig. 30", now 34" Fir, now snag with healed blazes, S.17°E., 59.4 ft.

Orig. 10" now 20" Fir, S.31°W., 9.2 ft. Alive, shows good scar. Do not open.

Orig. 36" now 37" Fir N.45°W., 25.7 ft., now snag with scribe on rotted face.

Set - Brass cap mkd: County Surveyors T24S R1W  
Office S 2|S 1  
1966 S 11|S 12

New BTs- 9" D.Fir N.44°W., 13.3 ft., mkd: T24S R1W S2 CS BT.

8" D.Fir N.22°E., 18.8 ft., mkd: T24S R1W S1 CS BT.

9" D.Fir S.85°E., 18.2 ft., mkd: T24S R1W S12 CS BT.