

TOWNSHIP 24 RANGE 01 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T24-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2775)

Set a basalt stone 12x10x10 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Fir 12" dia., bears N.26°E., 33 lks. dist. mkd. ¼ S BT.

A Fir 12" dia., bears N.55°W., 19 lks. dist. mkd. ¼ S BT.
Cor. is on a steep hillside, sloping W.

Glenn Baughman - For: U.S. Forest Service - Oct. 1980 - C.S. File 58/229-6

Found - 30" D.Fir stump, orig. BT, I opened to find scribe marks "BT", bears N.55°W., 12.5 ft.

26" D.Fir, Orig. BT, I opened to find scribe marks "4S", bears S.26°E., 21.8 ft. (Rec. N.26°E.)

Set a 2½" x 30" Iron pipe in the ground in a 3 ft. dia. mound of stone with a 3" brass cap mkd. "T24S ¼ R1W S36 S31 R1E 1980 LS 536."

New BTs- 11" D.Fir bears N.38°E., 33.6 ft. mkd. "¼ S31 BT" on a double blaze with a brass washer stamped "LS 536" nailed into lower blaze.

13" D.Fir bears N.11°W., 59.9 ft. mkd. "¼ S36 BT" on a double blaze with a brass washer stamped "LS 536" nailed into lower blaze.