

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2773)

Set a basalt stone 14x12x6 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 10" dia., bears S.28½°E., 40 lks. dist. mkd. ¼ S BT.
A Fir 36" dia., bears N.49°W., 58 lks. dist. mkd. ¼ S BT.
Cor. is on a steep hillside, sloping S.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
June 1965 - C.S. File 52/42-35

Found - Basalt stone 14x12x6" mkd. "¼" on W. face.
Orig. 10" now 18" Fir, S.28½°E., 26.4 ft. (face). We open and find "4" scribe. Alive.
Orig. 30" now 37" Fir N.49°W., 38.3 ft. (face), shows good scar. Alive.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S
R1W ¼ S25 | S30 R1E
1965

New BT - 9" Yew S.21°E., 19.7 ft. mkd. "¼ S30 DCS BT".
Corner is on the Douglas-Lane County Line.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
May 12, 1970 - C.S. File 54/27-206

Found - 1965 DCSO brass cap out of ground. Old Corner stone in place.
orig. 10" now 18" Fir, alive, S.28½°E., 26.4 ft.
"4" scribe visible on blaze, we open in 1965.
Orig. 30" now 37' Fir, alive, N.49°W., 38.3 ft., shows good scar, broken off about 60 ft. high.
9" Yew, alive, S.21°E., 19.7 ft. scribe OK, blaze split.

Reset 1" iron pipe/brass cap at corner and Reset old corner stone alongside.

New BTs- 18" Cedar S.18°W., 20.4 ft. mkd. ¼ S25 DCS BT.

16" Cedar S.44°E., 33.2 ft. mkd. ¼ S30 DCS BT.

Cor. lies on N-S cutting line, unit in sec. 25 and about 400 ft. N. of Chilcoot Creek.