

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T24-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2772-73)

Set a basalt stone 16x12x10 ins., 12" in the ground, for sec. cor. of secs. 19, 24, 25 and 30, marked with 4 notches on N. and 2 notches on S. edges; from which
A Fir 36" dia., bears N.60°E., 58 lks. dist. mkd. T24S R1E S19 BT.
A Fir 28" dia., bears N.78°W., 33 lks. dist. mkd. T24S R1W S25 BT.
A Fir 30" dia., bears S.58°E., 68 lks. dist. mkd. T24S R1E S30 BT.
A Fir 12" dia., bears N.79°W., 100 lks. dist. mkd. T24S R1W S24 BT.
Cor. is on a steep hillside, sloping NW. 75 ft. above creek.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 1965 - C.S. File 52/42-38

Found - Basalt stone 12 x 8 x 16" with 4 notches on N. edge and 2 notches on S. edge, firmly set.
Orig. 36" now 42" Fir, N.60°E., 38.3 ft. (face) alive, shows good scar.
Orig. 30" now 52" Fir, S.58°E., 44.9 ft. (face) alive, shows good scar.
Orig. 12" now 17" Fir, N.79°W., 66.0 ft. (face) alive, open and shows "T2W R S24 BT", rotting due to injury.

Set Brass cap at cor. mkd: County Surveyors Office
R1W

S 24	S 19
S 25	S 30

 R1E
1965

Set rock alongside.
New BTs- 10" Hemlock N.69°W., 19.9 ft. mkd. T24S R1W S24 DCS BT.
10" Hemlock S.73°W., 21.5 ft. mkd. T24S R1W S25 DCS BT.
Corner is on Douglas-Lane County Line.