

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T24-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2771)

-----

Set a basalt stone 14x12x10 ins., 10" in the ground for cor. of secs. 13, 18, 19, 24, marked with 3 notches on the N. and S. edges, from which

A Fir 60" dia., bears N.58°E., 7 lks. dist. mkd. T24S R1E S18 BT.

A Fir 20" dia., bears S.15½°E., 24 lks. dist. mkd. T24S R1E S19 BT.

A Fir 60" dia., bears S.74°W., 45 lks. dist. mkd. T24S R1W S24 BT.

A Cedar 22" dia., bears N.77°W., 64 lks. dist. mkd. T24S R1W S13 BT.

Cor. if on a steep hillside sloping SW.

Douglas Co. Surveyors office - Dennis Gaylord, U.S. Forest Service, Deputized by County; Travis Worthen, witness - Sept. 9, 1977 - C.S. File 59/40-5

-----

Found - A stone 7" x 12" x 14", lying on surface of ground. Three grooves on one face and three grooves on the opposite face.

Orig. 22" Cedar now 26", bears N.74°W., 42.24 ft. (Rec. N.77°W.) with healed blaze.

Orig. 60" D.Fir now 51", bears S.80°W., 29.7 ft. (Rec. S.74°W.) with healed blaze.

Orig. 20" Fir now a broken stob, bears S.19°30'E., 29.0 ft. (Rec. S.15°30'E., 15.84 ft.) True distance is 44 lks. not 24 lks. of record. Scribing visible "T 24 R1E S19 BT".

Orig. 60" D.Fir now 43", bears N.40°E., 4.62 ft. to center of tree. (Rec. N.58°E., 4.62 ft.) with healed blaze.

Set Brass cap 2½" dia. on 1" iron pipe marked.  
County Surveyor Office

T 24 S  
R S 13 | S 18 R  
1 S 24 | S 19 1  
W 1977 E

Built a mound of stone around cap, buried orig. stone alongside cap.

New BT - 30" D.Fir bears S.47°30'E., 45.4 ft. scribed T24S R1E S19 CS BT" on a double blaze.

Placed County BT tags on all five trees.